

17 Dynamic Routing Protocols - Answer Key

In this lab you will examine features which are common to all Interior Gateway Protocols. Basic configuration for various IGPs is included but is not the focus of this lab exercise. Configuration for each of the IGPs will be covered in detail later.

Routing Protocol Updates

- 1) Enter the commands below on each router to provision a basic RIPv1 configuration and enable RIP on every interface.

```
router rip
network 10.0.0.0
no auto-summary
```

- 2) Debug the routing protocol updates on R1. Observe the updates being sent and received. What kind of traffic is used (unicast, broadcast or multicast)?

The updates are being sent on the broadcast address 255.255.255.255. All hosts on the subnet must process the packets.

```
R1#debug ip rip
RIP protocol debugging is on
R1#
*Jul  4 03:43:55.455: RIP: sending v1 update to
255.255.255.255 via FastEthernet3/0 (10.0.3.1)
```

- 3) Enter the commands below to enable RIPv2 on every router.

```
router rip
version 2
```

- 4) What kind of traffic is used for the updates now?

The updates are being sent on the RIPv2 multicast address 224.0.0.9. Only RIPv2 routers will process the packets beyond layer 3.

```
*Jul  4 03:48:09.175: RIP: sending v2 update to 224.0.0.9
via FastEthernet3/0 (10.0.3.1)
```

5) Turn off all debugging on R1.

```
R1#undebug all
```

All possible debugging has been turned off

6) Check that RIP routes have been added to R1 and it has a route to every subnet in the lab.

```
R1#show ip route
```

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

Gateway of last resort is not set

```
10.0.0.0/8 is variably subnetted, 12 subnets, 2 masks
C    10.0.0.0/24 is directly connected, FastEthernet0/0
L    10.0.0.1/32 is directly connected, FastEthernet0/0
C    10.0.1.0/24 is directly connected, FastEthernet1/0
L    10.0.1.1/32 is directly connected, FastEthernet1/0
C    10.0.2.0/24 is directly connected, FastEthernet2/0
L    10.0.2.1/32 is directly connected, FastEthernet2/0
C    10.0.3.0/24 is directly connected, FastEthernet3/0
L    10.0.3.1/32 is directly connected, FastEthernet3/0
R    10.1.0.0/24 [120/1] via 10.0.0.2, 00:00:22, FastEthernet0/0
R    10.1.1.0/24 [120/2] via 10.0.3.2, 00:00:06, FastEthernet3/0
      [120/2] via 10.0.0.2, 00:00:22, FastEthernet0/0
R    10.1.2.0/24 [120/2] via 10.0.3.2, 00:00:06, FastEthernet3/0
R    10.1.3.0/24 [120/1] via 10.0.3.2, 00:00:06, FastEthernet3/0
```

7) Why are there two routes to the 10.1.1.0/24 network in the routing table?

Two paths to 10.1.1.0/24 have an equal metric – a hop count of 2. Both routes are installed in the routing table and the router will perform Equal Cost Load Balancing between the next hops of 10.0.3.2 and 10.0.0.2.

Comparing Routing Protocols

8) View the RIP database on R1.

```
R1#show ip rip database
10.0.0.0/8      auto-summary
10.0.0.0/24     directly connected, FastEthernet0/0
10.0.1.0/24     directly connected, FastEthernet1/0
10.0.2.0/24     directly connected, FastEthernet2/0
10.0.3.0/24     directly connected, FastEthernet3/0
10.1.0.0/24
  [1] via 10.0.0.2, 00:00:01, FastEthernet0/0
10.1.1.0/24
  [2] via 10.0.3.2, 00:00:15, FastEthernet3/0
  [2] via 10.0.0.2, 00:00:01, FastEthernet0/0
10.1.2.0/24
  [2] via 10.0.3.2, 00:00:15, FastEthernet3/0
10.1.3.0/24
  [1] via 10.0.3.2, 00:00:15, FastEthernet3/0
```

9) Enter the commands below on each router to provision a basic OSPF configuration and enable OSPF on every interface.

```
router ospf 1
network 10.0.0.0 0.255.255.255 area 0
```

10) Are RIP routes included in the routing table on R1? Why or why not?

The RIP routes are replaced by OSPF because its Administrative Distance of 110 is preferred to RIP's AD of 120.

```
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       + - replicated route, % - next hop override
```

Gateway of last resort is not set

```
10.0.0.0/8 is variably subnetted, 12 subnets, 2 masks
C      10.0.0.0/24 is directly connected, FastEthernet0/0
L      10.0.0.1/32 is directly connected, FastEthernet0/0
C      10.0.1.0/24 is directly connected, FastEthernet1/0
L      10.0.1.1/32 is directly connected, FastEthernet1/0
```

```

C      10.0.2.0/24 is directly connected, FastEthernet2/0
L      10.0.2.1/32 is directly connected, FastEthernet2/0
C      10.0.3.0/24 is directly connected, FastEthernet3/0
L      10.0.3.1/32 is directly connected, FastEthernet3/0
O      10.1.0.0/24 [110/2] via 10.0.0.2, 00:00:41, FastEthernet0/0
O      10.1.1.0/24 [110/3] via 10.0.0.2, 00:00:31, FastEthernet0/0
O      10.1.2.0/24 [110/4] via 10.0.0.2, 00:00:31, FastEthernet0/0
O      10.1.3.0/24 [110/13] via 10.0.0.2, 00:00:31, FastEthernet0/0

```

11) Why is there now only one route to the 10.1.1.0/24 network?

OSPF uses cost as its metric which takes into account interface bandwidth. The interfaces on R5 have a configured bandwidth of 10Mbps. The interfaces along the top path of the network topology all have the default FastEthernet bandwidth of 100Mbps so this route is preferred. All traffic will go via the next hop 10.0.0.2.

```

R5#show run interface f3/0
!
interface FastEthernet3/0
  bandwidth 10000
  ip address 10.0.3.2 255.255.255.0
  duplex full
end

```

12) Disable interface FastEthernet 0/0 on R2. What do you expect to happen to R1's routing table?

OSPF will reconverge. The routes to the 10.1.0.0 networks via R2 will be removed from the routing table and replaced with routes via R5.

```

R2(config)#interface fastEthernet 0/0
R2(config-if)#shutdown

```

13) Verify your expected changes to R1's routing table.

```

R1#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        + - replicated route, % - next hop override

```

Gateway of last resort is not set

```

      10.0.0.0/8 is variably subnetted, 12 subnets, 2 masks
C      10.0.0.0/24 is directly connected, FastEthernet0/0
L      10.0.0.1/32 is directly connected, FastEthernet0/0
C      10.0.1.0/24 is directly connected, FastEthernet1/0

```

```

L      10.0.1.1/32 is directly connected, FastEthernet1/0
C      10.0.2.0/24 is directly connected, FastEthernet2/0
L      10.0.2.1/32 is directly connected, FastEthernet2/0
C      10.0.3.0/24 is directly connected, FastEthernet3/0
L      10.0.3.1/32 is directly connected, FastEthernet3/0
O      10.1.0.0/24 [110/22] via 10.0.3.2, 00:00:27, FastEthernet3/0
O      10.1.1.0/24 [110/21] via 10.0.3.2, 00:00:27, FastEthernet3/0
O      10.1.2.0/24 [110/21] via 10.0.3.2, 00:00:27, FastEthernet3/0
O      10.1.3.0/24 [110/20] via 10.0.3.2, 00:00:27, FastEthernet3/0

```

14) Aside from the next hop address, what else has changed on the routing table?

The new routes have a higher metric. This is why they were not in the routing table when the path via R2 was up.

R1#sh ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
 D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
 N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
 E1 - OSPF external type 1, E2 - OSPF external type 2
 i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
 ia - IS-IS inter area, * - candidate default, U - per-user static route
 o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
 + - replicated route, % - next hop override

Gateway of last resort is not set

```

      10.0.0.0/8 is variably subnetted, 12 subnets, 2 masks
C      10.0.0.0/24 is directly connected, FastEthernet0/0
L      10.0.0.1/32 is directly connected, FastEthernet0/0
C      10.0.1.0/24 is directly connected, FastEthernet1/0
L      10.0.1.1/32 is directly connected, FastEthernet1/0
C      10.0.2.0/24 is directly connected, FastEthernet2/0
L      10.0.2.1/32 is directly connected, FastEthernet2/0
C      10.0.3.0/24 is directly connected, FastEthernet3/0
L      10.0.3.1/32 is directly connected, FastEthernet3/0
O      10.1.0.0/24 [110/22] via 10.0.3.2, 00:00:27, FastEthernet3/0
O      10.1.1.0/24 [110/21] via 10.0.3.2, 00:00:27, FastEthernet3/0
O      10.1.2.0/24 [110/21] via 10.0.3.2, 00:00:27, FastEthernet3/0
O      10.1.3.0/24 [110/20] via 10.0.3.2, 00:00:27, FastEthernet3/0

```

15) View the OSPF database on R1. What is different between it and the RIP database? Why?

RIP is a Distance Vector routing protocol so it only knows its directly connected neighbors and the lists of networks those neighbors have advertised.

OSPF is a Link State routing protocol so it knows the state of every link on every router in its area.

```
R1#show ip ospf database
```

OSPF Router with ID (10.0.3.1) (Process ID 1)

Router Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum	Link count
10.0.3.1	10.0.3.1	577	0x80000004	0x009EFB	4
10.1.0.2	10.1.0.2	614	0x80000003	0x00C538	1
10.1.1.2	10.1.1.2	1820	0x80000003	0x00626F	2
10.1.3.2	10.1.3.2	1046	0x80000003	0x00882A	2
203.0.113.1	203.0.113.1	1815	0x80000003	0x00AA9A	3

Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.0.3.1	10.0.3.1	1856	0x80000001	0x00A55A
10.1.0.1	10.1.1.2	1825	0x80000001	0x009371
10.1.1.1	203.0.113.1	1822	0x80000001	0x00EEB3
10.1.3.1	203.0.113.1	1816	0x80000001	0x00F2AB

Routing Protocol Metrics and Administrative Distance

16) Enter the command below to remove OSPF on every router

```
no router ospf 1
```

17) Will R1 still have connectivity to R4?

Yes. RIP is still running so RIP routes will replace the removed OSPF routes in the routing table.

```
R1#show ip route
```

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

Gateway of last resort is not set

```
10.0.0.0/8 is variably subnetted, 12 subnets, 2 masks
C    10.0.0.0/24 is directly connected, FastEthernet0/0
L    10.0.0.1/32 is directly connected, FastEthernet0/0
C    10.0.1.0/24 is directly connected, FastEthernet1/0
L    10.0.1.1/32 is directly connected, FastEthernet1/0
C    10.0.2.0/24 is directly connected, FastEthernet2/0
```

```

L      10.0.2.1/32 is directly connected, FastEthernet2/0
C      10.0.3.0/24 is directly connected, FastEthernet3/0
L      10.0.3.1/32 is directly connected, FastEthernet3/0
R      10.1.0.0/24 [120/3] via 10.0.3.2, 00:00:07, FastEthernet3/0
R      10.1.1.0/24 [120/2] via 10.0.3.2, 00:00:07, FastEthernet3/0
R      10.1.2.0/24 [120/2] via 10.0.3.2, 00:00:07, FastEthernet3/0
R      10.1.3.0/24 [120/1] via 10.0.3.2, 00:00:07, FastEthernet3/0

```

18) What is the metric to the 10.1.1.0/24 network on R1?

A hop count of 2.

19) Why is there only one route on R1 to the 10.1.1.0/24 network now?

Interface FastEthernet 0/0 on R2 is still shut down so no routes go through it.

20) Make the required change so that there are two routes to the 10.1.1.0/24 network in the routing table on R1.

```

R2(config)#interface f0/0
R2(config-if)#no shut

```

21) Enter the commands below on each router to provision a basic EIGRP configuration and enable EIGRP on every interface.

```

router eigrp 100
no auto-summary
network 10.0.0.0 0.255.255.255

```

22) What changes do you expect to see in the routing tables? Why?

The RIP routes will be replaced by EIGRP because its Administrative Distance of 90 is preferred to RIP's AD of 120.

23) Verify the changes to the routing table on R1.

```

R1#show ip route

```

```

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

```

```

Gateway of last resort is not set

```

```

      10.0.0.0/8 is variably subnetted, 12 subnets, 2 masks
C      10.0.0.0/24 is directly connected, FastEthernet0/0
L      10.0.0.1/32 is directly connected, FastEthernet0/0

```

```

C      10.0.1.0/24 is directly connected, FastEthernet1/0
L      10.0.1.1/32 is directly connected, FastEthernet1/0
C      10.0.2.0/24 is directly connected, FastEthernet2/0
L      10.0.2.1/32 is directly connected, FastEthernet2/0
C      10.0.3.0/24 is directly connected, FastEthernet3/0
L      10.0.3.1/32 is directly connected, FastEthernet3/0
D      10.1.0.0/24 [90/30720] via 10.0.0.2, 00:03:44, FastEthernet0/0
D      10.1.1.0/24 [90/33280] via 10.0.0.2, 00:03:33, FastEthernet0/0
D      10.1.2.0/24 [90/35840] via 10.0.0.2, 00:03:33, FastEthernet0/0
D      10.1.3.0/24 [90/261120] via 10.0.3.2, 00:03:33, FastEthernet3/0

```

24) What is the metric to the 10.1.1.0/24 network on R1?

A composite metric of 33280.

25) Why is there only one route to the 10.1.1.0/24 network on R1?

EIGRP uses a composite metric which takes into account interface bandwidth and delay. The interfaces on R5 have a configured bandwidth of 10Mbps. The interfaces along the top path of the network topology all have the default FastEthernet bandwidth of 100Mbps so this route is preferred. All traffic will go via the next hop 10.0.0.2.

26) Disable RIP and EIGRP on R5 with the commands below.

```

R5(config)#no router rip
R5(config)#no router eigrp 100

```

27) Configure the network so that there is still connectivity between all subnets if the link between R1 and R2 goes down. Accomplish this with six commands. Do not enable EIGRP on R5 but note that the routing protocol is expected to be enabled there in the future.

Floating static routes need to be added as a backup to the EIGRP routes. We want to ensure EIGRP routes are preferred when available so set the AD to be higher than EIGRP's AD of 90.

```

R1(config)#ip route 10.1.0.0 255.255.0.0 10.0.3.2 95
R2(config)#ip route 10.0.0.0 255.255.0.0 10.1.0.1 95
R3(config)#ip route 10.0.0.0 255.255.0.0 10.1.1.1 95
R4(config)#ip route 10.0.0.0 255.255.0.0 10.1.3.2 95
R5(config)#ip route 10.0.0.0 255.255.0.0 10.0.3.1 95
R5(config)#ip route 10.1.0.0 255.255.0.0 10.1.3.1 95

```

R5 is not running EIGRP so it is not currently necessary to set the Administrative Distance for its routes to 95. It is required to prevent the floating static routes from being preferred when EIGRP is enabled in the future however.

Summary routes need to be used to accomplish the task in six commands.

28) What changes do you expect to see to the routing table on R1?

The summary route will be added to the routing table but not used because it has a prefix length of /16, compared to the EIGRP routes which have a longer prefix length of /24.

If individual floating static routes had been added for each of the /24 destination networks then these would not have appeared in the routing table (unless a link went down) because EIGRP has a better Administrative Distance.

29) Verify the changes to the routing table on R1.

R1#sh ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

Gateway of last resort is not set

```

      10.0.0.0/8 is variably subnetted, 13 subnets, 3 masks
C       10.0.0.0/24 is directly connected, FastEthernet0/0
L       10.0.0.1/32 is directly connected, FastEthernet0/0
C       10.0.1.0/24 is directly connected, FastEthernet1/0
L       10.0.1.1/32 is directly connected, FastEthernet1/0
C       10.0.2.0/24 is directly connected, FastEthernet2/0
L       10.0.2.1/32 is directly connected, FastEthernet2/0
C       10.0.3.0/24 is directly connected, FastEthernet3/0
L       10.0.3.1/32 is directly connected, FastEthernet3/0
S       10.1.0.0/16 [95/0] via 10.0.3.2
D       10.1.0.0/24 [90/30720] via 10.0.0.2, 00:35:41, FastEthernet0/0
D       10.1.1.0/24 [90/33280] via 10.0.0.2, 00:35:30, FastEthernet0/0
D       10.1.2.0/24 [90/35840] via 10.0.0.2, 00:35:30, FastEthernet0/0
D       10.1.3.0/24 [90/266240] via 10.0.0.2, 00:25:14, FastEthernet0/0
```

30) Verify that traffic from PC1 to PC3 still goes via R2.

PC1> trace 10.1.2.10

trace to 10.1.2.10, 8 hops max, press Ctrl+C to stop

1	10.0.1.1	29.169 ms	8.005 ms	9.006 ms
2	10.0.0.2	28.020 ms	29.526 ms	28.522 ms
3	10.1.0.1	49.034 ms	49.043 ms	49.030 ms
4	10.1.1.1	80.063 ms	80.057 ms	68.046 ms

```
5    *10.1.2.10    110.046 ms (ICMP type:3, code:3,  
Destination port unreachable)
```

31) Shut down interface FastEthernet 0/0 on R2.

```
R2(config)#interface f0/0  
R2(config-if)#shutdown
```

32) What changes do you expect to see on R1's routing table?

The EIGRP routes will be removed.

33) Verify the changes to the routing table on R1.

```
R1#show ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP  
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
        E1 - OSPF external type 1, E2 - OSPF external type 2  
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS  
level-2  
        ia - IS-IS inter area, * - candidate default, U - per-user static  
route  
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP  
        + - replicated route, % - next hop override
```

Gateway of last resort is not set

```
      10.0.0.0/8 is variably subnetted, 9 subnets, 3 masks  
C       10.0.0.0/24 is directly connected, FastEthernet0/0  
L       10.0.0.1/32 is directly connected, FastEthernet0/0  
C       10.0.1.0/24 is directly connected, FastEthernet1/0  
L       10.0.1.1/32 is directly connected, FastEthernet1/0  
C       10.0.2.0/24 is directly connected, FastEthernet2/0  
L       10.0.2.1/32 is directly connected, FastEthernet2/0  
C       10.0.3.0/24 is directly connected, FastEthernet3/0  
L       10.0.3.1/32 is directly connected, FastEthernet3/0  
S       10.1.0.0/16 [95/0] via 10.0.3.2
```

34) Verify connectivity between PC1 and PC3.

```
PC1> ping 10.1.2.10  
84 bytes from 10.1.2.10 icmp_seq=1 ttl=61 time=56.766 ms  
84 bytes from 10.1.2.10 icmp_seq=2 ttl=61 time=54.036 ms  
84 bytes from 10.1.2.10 icmp_seq=3 ttl=61 time=56.171 ms  
84 bytes from 10.1.2.10 icmp_seq=4 ttl=61 time=57.038 ms  
84 bytes from 10.1.2.10 icmp_seq=5 ttl=61 time=59.176 ms
```

35) Verify the traffic goes via R5.

```
PC1> trace 10.1.2.10
trace to 10.1.2.10, 8 hops max, press Ctrl+C to stop
 1  10.0.1.1    9.005 ms  9.005 ms  9.008 ms
 2  10.0.3.2   28.018 ms  28.530 ms  29.184 ms
 3  10.1.3.1   49.033 ms  50.161 ms  49.036 ms
 4  *10.1.2.10 59.220 ms (ICMP type:3, code:3,
Destination port unreachable)
```

36) Bring interface FastEthernet 0/0 on R2 back up.

```
R2(config)#interface f0/0
R2(config-if)#no shutdown
```

37) Enter the commands below on R5 to provision a basic EIGRP configuration and enable EIGRP on every interface.

```
R5(config)#router eigrp 100
R5(config-router)#no auto-summary
R5(config-router)#network 10.0.0.0 0.255.255.255
```

Loopback Interfaces

38) Configure loopback interface 0 on each router. Assign the IP address 192.168.0.x/32, where 'x' is the router number (for example 192.168.0.3/32 on R3.)

```
R1(config)#interface loopback0
R1(config-if)#ip address 192.168.0.1 255.255.255.255
```

```
R2(config)#interface loopback0
R2(config-if)#ip address 192.168.0.2 255.255.255.255
```

```
R3(config)#interface loopback0
R3(config-if)#ip address 192.168.0.3 255.255.255.255
```

```
R4(config)#interface loopback0
R4(config-if)#ip address 192.168.0.4 255.255.255.255
```

```
R5(config)#interface loopback0
R5(config-if)#ip address 192.168.0.5 255.255.255.255
```

39) Is there connectivity to the loopback interfaces from the PCs? Why or why not?

There is no connectivity from the PCs to the loopback interfaces because they are not in the routing tables of the routers (apart from the local loopback interface on each router). The loopback interfaces are not in the routing tables because they are in the 192.168.0.0/24 range which has not been included in the routing protocol.

```
R1#sh ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        + - replicated route, % - next hop override
```

Gateway of last resort is not set

```
      10.0.0.0/8 is variably subnetted, 13 subnets, 3 masks
C       10.0.0.0/24 is directly connected, FastEthernet0/0
L       10.0.0.1/32 is directly connected, FastEthernet0/0
C       10.0.1.0/24 is directly connected, FastEthernet1/0
L       10.0.1.1/32 is directly connected, FastEthernet1/0
C       10.0.2.0/24 is directly connected, FastEthernet2/0
L       10.0.2.1/32 is directly connected, FastEthernet2/0
C       10.0.3.0/24 is directly connected, FastEthernet3/0
L       10.0.3.1/32 is directly connected, FastEthernet3/0
S       10.1.0.0/16 [95/0] via 10.0.3.2
D       10.1.0.0/24 [90/30720] via 10.0.0.2, 00:05:10, FastEthernet0/0
D       10.1.1.0/24 [90/33280] via 10.0.0.2, 00:03:12, FastEthernet0/0
D       10.1.2.0/24 [90/35840] via 10.0.0.2, 00:03:12, FastEthernet0/0
D       10.1.3.0/24 [90/261120] via 10.0.3.2, 00:03:12, FastEthernet3/0
      192.168.0.0/32 is subnetted, 1 subnets
C       192.168.0.1 is directly connected, Loopback0
```

40) Enter the commands below on each router to include the loopback interfaces in EIGRP.

```
R1(config)#router eigrp 100
```

```
R1(config-router)#network 192.168.0.0 0.0.0.255
```

41) Verify the loopback interfaces are in the routing table on R1.

```
R1#sh ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
        E1 - OSPF external type 1, E2 - OSPF external type 2
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
        ia - IS-IS inter area, * - candidate default, U - per-user static route
        o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
        + - replicated route, % - next hop override
```

Gateway of last resort is not set

```
10.0.0.0/8 is variably subnetted, 13 subnets, 3 masks
C    10.0.0.0/24 is directly connected, FastEthernet0/0
L    10.0.0.1/32 is directly connected, FastEthernet0/0
C    10.0.1.0/24 is directly connected, FastEthernet1/0
L    10.0.1.1/32 is directly connected, FastEthernet1/0
C    10.0.2.0/24 is directly connected, FastEthernet2/0
L    10.0.2.1/32 is directly connected, FastEthernet2/0
C    10.0.3.0/24 is directly connected, FastEthernet3/0
L    10.0.3.1/32 is directly connected, FastEthernet3/0
S    10.1.0.0/16 [95/0] via 10.0.3.2
D    10.1.0.0/24 [90/30720] via 10.0.0.2, 00:11:46, FastEthernet0/0
D    10.1.1.0/24 [90/33280] via 10.0.0.2, 00:09:48, FastEthernet0/0
D    10.1.2.0/24 [90/35840] via 10.0.0.2, 00:09:48, FastEthernet0/0
D    10.1.3.0/24 [90/261120] via 10.0.3.2, 00:09:48, FastEthernet3/0
192.168.0.0/32 is subnetted, 5 subnets
C    192.168.0.1 is directly connected, Loopback0
D    192.168.0.2 [90/156160] via 10.0.0.2, 00:00:17, FastEthernet0/0
D    192.168.0.3 [90/158720] via 10.0.0.2, 00:00:12, FastEthernet0/0
D    192.168.0.4 [90/161280] via 10.0.0.2, 00:00:09, FastEthernet0/0
D    192.168.0.5 [90/386560] via 10.0.3.2, 00:00:05, FastEthernet3/0
```

42) Verify connectivity from PC1 to the loopback interface on R5.

```
PC1> ping 192.168.0.5
84 bytes from 192.168.0.5 icmp_seq=1 ttl=254 time=25.015 ms
84 bytes from 192.168.0.5 icmp_seq=2 ttl=254 time=24.032 ms
84 bytes from 192.168.0.5 icmp_seq=3 ttl=254 time=28.027 ms
84 bytes from 192.168.0.5 icmp_seq=4 ttl=254 time=29.023 ms
84 bytes from 192.168.0.5 icmp_seq=5 ttl=254 time=27.019 ms
```

Adjacencies and Passive Interfaces

43) Enter the command below to verify that R1 has established EIGRP adjacencies with R2 and R5.

```
R1#show ip eigrp neighbors
EIGRP-IPv4 Neighbors for AS(100)
H   Address                Interface      Hold Uptime    SRTT   RTT  Q  Seq
                               (sec)          (ms)                Cnt  Num
1   10.0.3.2                Fa3/0         14 00:17:21    33    198  0   16
0   10.0.0.2                Fa0/0         11 00:19:21    36    216  0   32
```

44) Verify that traffic from R5 to the directly connected interfaces on R1 goes via the FastEthernet 3/0 interface.

```
R5#show ip route
```

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2

ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

Gateway of last resort is not set

```

10.0.0.0/8 is variably subnetted, 12 subnets, 3 masks
S    10.0.0.0/16 [95/0] via 10.0.3.1
D    10.0.0.0/24 [90/261120] via 10.0.3.1, 00:23:01, FastEthernet3/0
D    10.0.1.0/24 [90/261120] via 10.0.3.1, 00:23:01, FastEthernet3/0
D    10.0.2.0/24 [90/261120] via 10.0.3.1, 00:23:01, FastEthernet3/0
C    10.0.3.0/24 is directly connected, FastEthernet3/0
L    10.0.3.2/32 is directly connected, FastEthernet3/0
S    10.1.0.0/16 [95/0] via 10.1.3.1
D    10.1.0.0/24 [90/263680] via 10.1.3.1, 00:23:01, FastEthernet2/0
      [90/263680] via 10.0.3.1, 00:23:01, FastEthernet3/0
D    10.1.1.0/24 [90/261120] via 10.1.3.1, 00:23:01, FastEthernet2/0
D    10.1.2.0/24 [90/261120] via 10.1.3.1, 00:23:01, FastEthernet2/0
C    10.1.3.0/24 is directly connected, FastEthernet2/0
L    10.1.3.2/32 is directly connected, FastEthernet2/0
192.168.0.0/32 is subnetted, 5 subnets
D    192.168.0.1 [90/386560] via 10.0.3.1, 00:15:05, FastEthernet3/0
D    192.168.0.2 [90/389120] via 10.0.3.1, 00:13:29, FastEthernet3/0
D    192.168.0.3 [90/389120] via 10.1.3.1, 00:13:25, FastEthernet2/0
D    192.168.0.4 [90/386560] via 10.1.3.1, 00:13:22, FastEthernet2/0
C    192.168.0.5 is directly connected, Loopback0

```

45) Enter the commands below to configure the loopback interface and the link to R5 as passive interfaces on R1.

```

R1(config-if)#router eigrp 100
R1(config-router)#passive-interface loopback0
R1(config-router)#passive-interface fastethernet3/0

```

46) What changes do you expect to see in the routing table on R5 and why?

The EIGRP adjacency between R1 and R5 will go down. All EIGRP routes via R1 will be removed from the routing table and replaced with routes via R4. Configuring the loopback interface as a passive interface on R1 does not affect any routing tables but is a best practice.

47) Verify the expected changes to the routing table on R5.

```

R5#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
+ - replicated route, % - next hop override

```

Gateway of last resort is not set

```

10.0.0.0/8 is variably subnetted, 12 subnets, 3 masks
S    10.0.0.0/16 [95/0] via 10.0.3.1

```

```

D      10.0.0.0/24 [90/266240] via 10.1.3.1, 00:04:24, FastEthernet2/0
D      10.0.1.0/24 [90/268800] via 10.1.3.1, 00:04:24, FastEthernet2/0
D      10.0.2.0/24 [90/268800] via 10.1.3.1, 00:04:24, FastEthernet2/0
C      10.0.3.0/24 is directly connected, FastEthernet3/0
L      10.0.3.2/32 is directly connected, FastEthernet3/0
S      10.1.0.0/16 [95/0] via 10.1.3.1
D      10.1.0.0/24 [90/263680] via 10.1.3.1, 00:04:24, FastEthernet2/0
D      10.1.1.0/24 [90/261120] via 10.1.3.1, 00:33:20, FastEthernet2/0
D      10.1.2.0/24 [90/261120] via 10.1.3.1, 00:33:20, FastEthernet2/0
C      10.1.3.0/24 is directly connected, FastEthernet2/0
L      10.1.3.2/32 is directly connected, FastEthernet2/0
192.168.0.0/32 is subnetted, 5 subnets
D      192.168.0.1 [90/394240] via 10.1.3.1, 00:04:24, FastEthernet2/0
D      192.168.0.2 [90/391680] via 10.1.3.1, 00:04:24, FastEthernet2/0
D      192.168.0.3 [90/389120] via 10.1.3.1, 00:23:44, FastEthernet2/0
D      192.168.0.4 [90/386560] via 10.1.3.1, 00:23:41, FastEthernet2/0
C      192.168.0.5 is directly connected, Loopback0

```